

Morsø 3610 Ribbed

A choice for life.

When you eventually put this literature down, the likelihood is you'll be sold. You'll have fallen for Morsø's timeless look. You'll have fallen in love with cast iron's unique properties. And you'll be convinced of our stoves' obvious advantages for the environment.

But believe us – when you describe your relationship with your Morsø in the future, it won't be the design, the cast iron or the stove's green-friendly impact which will fuel your fondness. By then, your stove will have already become one of the most loved items of furniture in your home. A trusty source of comfort, you will love it for its sound, look and warmth. And for the glow of happiness it has spread throughout the house year after year. To choose a Morsø is, in other words, to make a choice for life.



The **Morsø 3610 stove** is one of the largest Morso stove producing a nominal 10 kw output. A beautifully designed stove with clean lines, the Morso 3610 radiant stove is ideal for rooms with cathedral ceilings that require a radiant heater for effective and efficient heating. In addition, this stove's large double doors make it perfect for heating large rooms.

The primary air-control lever is conveniently located in the front of the stove making it easy to adjust heat output and burn time, and the double doors with extra-large glass panels provide an excellent view of the fire. To keep the large panels clean, primary air is designed to "wash" down across the glass panes to keep them clean through all phases of the burn cycle.



Wood can be loaded into a Morso 3610 stove from the front doors or through the easy-access side door. The large firebox accepts up to 58 cm logs and a specifically designed air channel helps burn the fuel as completely and efficiently as possible. The Morso 3610 has two ash pans for convenient ash removal without manually shovelling out the ashes from the firebox.

Installation of the Morso 3610 is versatile and flexible with a reversible Ø155 mm flue collar, rear and bottom heat shields are standard.

- Rated output: 10kW
- Heat output range: 6-14kW
- Heats up m²: 210m²
- Height: 796mm
- Width: 598mm
- Depth: 505mm
- Flue diameter: 150Ø
- Weight: 220kg

